

Coolant**PETRONAS Tutela Coolant LL Premix****Range:**

Long description: PETRONAS Tutela Coolant LL Premix is a premium performance ready to use Long-Life Coolant delivering optimized performance and component durability for vehicle cooling systems. Formulated with Mono-Ethylene Glycol enhanced with a special Organic Acid salts inhibitor (OAT Technology), free of nitrites, borates, phosphates, silicates and amines, it provides excellent protection against overheating, frost and corrosion. Thanks to its wide OEMs coverage, it is suitable for most European, American and Asian passenger cars, commercial vehicles and agriculture machinery.

[Product data sheet](#) [Safety data sheet](#)

Industry Specifications: AFNOR NFR 15-601 AS 2108-2004 ASTM D 3306 ASTM D 6210 BS 6580:2010 CUNA 956-16 ONORM V 5123 SAE J1034 SANS 1251:2005 SH 0521-1999

OEM Performance - Only for Automotive: CNHi MAT 3724 CNHi MAT 3624 DAF (MAT 74002) Daimler/Mercedes-Benz 325.3 Fiat 9.55523 IVECO 18-1830 MAN 324 Type SNF MTU MTL 5048 Porsche from MY 1996 to MY 2010 PSA B71 5110 VW/Audi/Seat/Skoda TL 774-D/F

Application(s) - For Consumers pages: Passenger car

Sector(s) - For Businesses page: Road Transport